


Location: _____



FHA, FHG

FLOOR ACCESS DOOR

Specification: MIFAB® Series FHA and FHG floor access doors are for interior or exterior use where easy access is required. The angle frame construction with integral anchor flange is designed to be cast into concrete. Available in either an acid resistant, powder epoxy coated steel (grey color) (FHG) or aluminum (FHA). Standard units withstand load bearing of 300 lbs. per square foot. MIFAB's floor access doors are designed for safety, durability and ease of operation.



- Material:** FHG Series has a door made of 3/16" (5) thick A36 diamond plate. FHA Series has a door made of 3/16" (5) thick structural grade aluminum diamond plate. Both doors can support 300 lbs. per square foot live load. Frame material is composite hot rolled steel angle frame.
- Finish:** FHG Series is an acid resistant, powder epoxy coated steel (grey color). FHA Series is an aluminum mill finish. Frame is finished with a bituminous coating.
- Door:** Flush to frame. Equipped with an automatically locking hold open arm that locks the door in the open position. Also available are 1/4" (6 mm) thick doors reinforced to meet a 10,000 lb. load rating. (without impact for the FHA Series).
- Frame:** Complete with a 1" (25) anchor flange. All hardware is Type # 316 stainless steel.
- Hinge:** Tamper proof steel hinges with stainless steel pins.
- Opening Device:** Automatic locking hold open arm with red vinyl grip allows door to open 90 degrees.
- Handle:** Stainless steel recessed lift handle in the door.
- Latch:** The following lock options are available: padlock staple, Type # 316 stainless steel snap lock with removable handle, recessed hasp, Type # 316 stainless steel pentahead, keyed deadbolt lock or hasp and staple. The standard latch used is the compression lever latch (illustrated below).
- Packaging:** Individual pack.

"B" x "A" DOOR OPENING	FLOOR OPENING	FHA SHIPPING WT.	FHG SHIPPING WT.	GALVANIZED MODEL #	ALUMINUM MODEL #
24" x 24"	26-1/2" x 24-1/2"	(Lbs.)	(Lbs.)	FHG2424	FHA2424
24" x 30"	26-1/2" x 30-1/2"	42.0	90.0	FHG2430	FHA2430
24" x 36"	26-1/2" x 36-1/2"	49.0	105.0	FHG2436	FHA2436
30" x 30"	32-1/2" x 30-1/2"	55.0	120.0	FHG3030	FHA3030
30" x 36"	32-1/2" x 36-1/2"	56.0	122.0	FHG3036	FHA3036
30" x 48"	32-1/2" x 48-1/2"	64.0	138.0	FHG3048	FHA3048
36" x 36"	38-1/2" x 36-1/2"	78.0	172.0	FHG3636	FHA3636
36" x 48"	38-1/2" x 48-1/2"	72.0	156.0	FHG3648	FHA3648
42" x 42"	44-1/2" x 42-1/2"	89.0	194.0	FHG4242	FHA4242
48" x 48"	50-1/2" x 48-1/2"	90.0	196.0	FHG4848	FHA4848
48" x 72"	50-1/2" x 72-1/2"	108.0	240.0	FHG4872	FHA4872
60" x 60"	62-1/2" x 60-1/2"	150.0	332.0	FHG6060	FHA6060




SUFFIX OPTIONAL VARIATIONS

- BA Buy American Act compliant product
- PA Pennsylvania Steel Act compliant product

Optional Accessories:

- Compression Spring Assist
- Skirting to Depth of Slab
- Fibreglass Insulation
- Safety Chains and Posts
- Access Nets - Safety Net System
- Hoists
- Bolt-on Style Ladders
- Recess Frame (Suffix -RF)



(Dimension) Denotes Millimetres

Note: The hinge is always furnished on the "A" or height (longer) dimension, unless otherwise specified.

Example: the model number would be FHG4872 for a floor access door with the hinge on the longer (72") dimension. The model number would be FHG7248 for a floor access door with the hinge on the shorter (48") dimension.

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____